

WARRANTY CERTIFICATE

DYNAMIC®

FIRM-SET, MODIFIED TRANSITIONAL PRESSURE SENSITIVE ADHESIVE

W.F. Taylor LLC (herein Taylor) provides a 10-year limited adhesive bond warranty when Dynamic® is used for the interior installation of approved flooring products over properly prepared substrates (see current technical data sheet for complete details). Dynamic® shall be free from manufacturing defects and will perform as designed when properly used.

Substrates shall be properly prepared per ASTM F710, have an intact moisture vapor retarder per ASTM E1745, and be without hydrostatic pressure. The installation must be performed following both the flooring manufacturer's and Taylor's guidelines. For the latest product information and application instructions please visit www.tayloradhesives.com.

If an installation failure occurs as a direct result of the use of defective Dynamic®, Taylor will pay for equivalent floor covering, replacement Dynamic®, and for reasonable labor costs to repair or replace the failed portion of the installation as determined by Taylor at its sole discretion. This warranty applies only to Dynamic® related bond failures. Taylor cannot warrant those variables over which it has no control such as the quantity of Dynamic® used, the workmanship of the installer, the condition of the subfloor, excessive moisture, excessive pH, the stability of the flooring product and its suitability for installation on the affected job-site, or any other conditions that might affect the installation.

Taylor reserves the right as deemed necessary to inspect any claim for cause or this warranty is null and void. Any repairs done prior to inspection by a Taylor representative voids any warranty. This warranty is non-transferable.

