

ELEVATE

ROLLER APPLIED WALL ADHESIVE FOR VINYL
PLANK/TILE

SIGNATURE LINE®

TECHNICAL DATA SHEET

April 2025
Version 3.2

RESIDENTIAL

MULTI-FAMILY

COMMERCIAL

DESCRIPTION

Elevate is an adhesive designed to install LVT and LVP to walls.

APPROVED WALL COVERING

Dryback LVP/LVT with a maximum thickness of 2mm and a smooth/non-embossed backing.

PRECAUTIONARY NOTES:

- TAYLOR cannot be held liable for the type of products adhered to the wall.
- Verify burn rating results prior to installation (check with the flooring manufacturer and the local state authorities).
- Not suitable for locking products.

APPROVED SUBSTRATES & SURFACES

- Smooth (non-textured) walls free of loose paint and/or other contaminants such as dust, wax, oil or grease.
- Drywall or gypsum board primed with a universal primer or flat paint.

PRECAUTIONARY NOTES:

- Avoid installing in areas exposed to direct sunlight.
- Avoid installing in wet areas such as showers.
- Avoid installing over glossy paint surfaces.

SUBSTRATE & SURFACE PREPARATION

Follow LVP/LVT manufacturer's guidelines for all applicable federal, state, and local fire/burn regulations. Substrate must be properly prepared including, but not limited to the following:

- Walls must be dry, clean, smooth and structurally sound. They shall be free of any foreign materials that might prevent adhesive bond, including dust, dirt, solvent, paint, wax, oil, grease, residual adhesive, adhesive removers, incompatible sealers, fire-retardant chemicals, fungicides, release agents, mold, and mildew.
- Fill all surface cracks, grooves, and depressions with drywall patching compounds, allow to fully cure and correct high spots before applying adhesive.
- The substrate, adhesive and LVP/LVT must be acclimated in an enclosed building with the HVAC operational at service temperature, between 60-95°F (15-35°C), and between 30-65% relative humidity, for at least 72 hours prior to, during, and permanently after installation.

PRECAUTIONARY NOTE:

- The wall should be primed or painted with a flat latex based paint prior to application.

APPLICATION INSTRUCTIONS

Follow LVP/LVT manufacturer's guidelines for layout, design and any special precautions for installation. Plan your installation pattern before placing tile into the adhesive and avoid repositioning.

1. Spread adhesive using required tools.
 - Apply adhesive directly to the wall.
 - Ensure 100% coverage with a thick, even film of adhesive.
2. Install LVP/LVT (flash and working times dependent upon temperature and humidity).
 - Wait 30-60 minutes after adhesive is spread to allow flash off.
 - Working time is approximately 2 hours.
3. Roll and cross roll LVP/LVT with an extension wall roller to ensure proper transfer of adhesive.
 - Re-roll the entire wall immediately after completion to ensure proper contact with the adhesive.

TAYLOR TECHNICAL SERVICES

706.712.5823
tech@tayloradhesives.com
3343 Dug Gap Road, Dalton, GA 30721

TAYLOR
ADHESIVES
A Meridian Brand

PRECAUTIONARY NOTE:

- Reseal lid when not in use to protect product.

REQUIRED TOOLS AND COVERAGE

*Coverage is approximate and may vary depending on porosity of substrate.

WALL COVERING TYPES	TOOL* (IMAGES NOT TO SCALE)		ESTIMATED COVERAGE
BOND ONLY			
Approved LVP, LVT	3/8" Short Nap Paint Roller		250-300 ft²/gal

*It is the sole responsibility of the contractor/installer to determine the proper preparation of the wall, apply the correct amount of adhesive for the job conditions and ensure that all instructions, procedures and practices are strictly adhered to.

CLEANING INSTRUCTIONS

While product is still wet: Use a damp cloth and water to remove.

While product is still soft: denatured alcohol, mineral spirits, or an adhesive remover/stripper. Always check compatibility on a piece of scrap wall covering.

STORAGE

This product should be stored at temperatures between 50-90°F (15-32°C). While this product is freeze-thaw stable, it is recommended to protect it from freezing. Freeze/thaw stable to 10°F (-12°C).

CAUTION

DO NOT take internally. If swallowed, DO NOT induce vomiting. Call a physician immediately. KEEP OUT OF REACH OF CHILDREN.

WARRANTY INFORMATION

For warranty information, call Technical Services at **706-712-5823**, visit us on the web at **www.tayloradhesives.com** or e-mail us at **tech@tayloradhesives.com**. Flooring manufacturer's and TAYLOR's written pre-installation and installation instructions must be strictly followed or the TAYLOR warranty will be void.

TAYLOR TECHNICAL SERVICES

 706.712.5823
 tech@tayloradhesives.com
 3343 Dug Gap Road, Dalton, GA 30721

 **TAYLOR**[™]
ADHESIVES
A Meridian Brand

ELEVATE PRODUCT INFORMATION		
PRODUCT CHARACTERISTICS	Product Classification	Roller Applied Wall Adhesive For Vinyl Plank/Tile
	Base Chemistry	Synthetic latex blend
	Curing Method	Evaporation
	Appearance/Color	Off-white (wet), clear/translucent (dry)
	Odor	Extremely low
	Consistency	Smooth medium viscosity liquid
	Application	Easy rolling
	Flammability	Non-flammable
	Freeze/Thaw	Stable to 10°F (-12°C) [3 cycles]
	Shelf Life [Unopened Container at 70°F]	2 years
TESTING	Moisture Control	No
	RH [ASTM F2170]	N/A
	pH	N/A
	MVER [ASTM F1869]	N/A
	Porosity [ASTM F3191]	N/A
TIME	Open Time	N/A
	Flash Time	30-60 min
	Working Time	2 hrs
	Cure Time	12 hrs
	Pot Life	N/A
TRAFFIC	Light Traffic	N/A
	Heavy Traffic	N/A
	Heavy Rolling Loads	N/A
ACOUSTICS*	STC	N/A
	IIC	N/A
	Delta IIC	N/A
SUSTAINABILITY	Solvents	No
	Isocyanates	No
	VOC Wet Applied [g/L] [SCAQMD Rule #1168]	< 8 g/L
	Bio-Based Content	No
	Post-Consumer Recycled Content	No
	Mineral Abundant Content	Yes
	LEED v4/4.1 Points	Pending
	Certifications	FloorScore
	Transparency	USGBC Member
WARRANTY**	Duration (non CFI Certified)	10-Year Performance Warranty
	Duration (CFI Certified)	Lifetime Performance Warranty
	Coverage	Bond

**For warranty information, view Product Warranty Certificate.